

Power	20kW	40kW	30kW	60KW
Input Voltage	3-phase 400V ±15% AC			
Input Voltage Type	TN-S (Three Phase Five Wire)			
Working Frequency	45~65Hz			
Power Factor	≥0.99			
Efficiency	≥94%			
Rated Voltage	CHAdeMO 500Vdc; CCS 750Vdc; GBT 750Vdc		CHAdeMO 500Vdc; CCS 1000Vdc; GBT 1000Vdc	

Max. Output Current	66A	132A	100A	200A
Display	8" LCD Touch Screen			
Language	Chinese, English, French, German, Spanish, Russian, etc.			
Payment	Mobile APP/RFID/POS			
Network Connection	4G(GSM or CDMA)/Ethernet			
Communication Protocols	OCPP1.6J or OCPP2.0			
Working Temperature	-30°C ~ +55°C			
Storage Temperature	-35°C ~ +55°C			

Operating Humidity	≤95% Non-Condensing			
Protection	IP54			
Acoustic Noise	<60dB			
Cooling Method	Forced Air-Cooling			
Dimension(W x D x H)	690mm*584mm*1686mm (±20mm)			
No. of Charging Cable	Single	Dual	Single	Dual
Cable Length	5m or 7m			
Certificate	TUV CE/IEC61851-1/IEC61851-23/IEC61851-21-2			